

// This Pine Script® code is subject to the terms of the Mozilla Public License 2.0 at <https://mozilla.org/MPL/2.0/>

//@version=6

indicator("MFB - Value Reading Session", overlay = true, max_bars_back = 5000, max_lines_count = 500, max_labels_count = 500)

// --- Settings ---

// Anchored to the previous day's RTH session (9:30am - 4:00pm).

sessionTime = input.session("0930-1600", "Structural Session", tooltip = "The time range of the previous day used for context (Institutional RTH).")

timezoneInput = input.string("America/New_York", "Timezone", tooltip = "Timezone used for the session calculation.")

valueAreaPct = input.float(70.0, "Value Area Percentage", minval = 0, maxval = 100, tooltip = "Percentage of total volume included in the value area.") / 100.0

rowCount = input.int(50, "Row Resolution", minval = 10, maxval = 100, tooltip = "Number of price rows used to build the volume profile.")

histWidth = input.int(40, "Histogram Width (Bars)", minval = 5, maxval = 200, tooltip = "Maximum horizontal width of the volume histogram.")

labelSize = input.string(size.normal, "Label Size", options = [size.small, size.normal, size.large, size.huge], tooltip = "Size used for profile labels.")

showAwarenessInput = input.bool(false, "Show Awareness Box", tooltip = "When enabled, displays the value-reading rules in a chart information box. It is hidden by default.")

showReadingInput = input.bool(true, "Show Value Reading", tooltip = "Controls whether the Bullish, Bearish, or Mixed / Probability Magnet reading appears during the active NY session.")

```
awarenessBoxPositionInput = input.string(position.middle_right, "Awareness  
Box Position", options = [position.top_left, position.top_center,  
position.top_right, position.middle_left, position.middle_center,  
position.middle_right, position.bottom_left, position.bottom_center,  
position.bottom_right], tooltip = "Select where the Awareness Box is anchored  
on the chart.")
```

```
awarenessBoxWidthInput  = input.float(0.0, "Awareness Box Width %", minval  
= 0.0, maxval = 80.0, tooltip = "Use 0 for automatic width that fits the text.  
Enter a percentage above 0 to set a fixed box width.")
```

```
awarenessTextSizeInput  = input.string(size.normal, "Awareness Text Size",  
options = [size.small, size.normal, size.large, size.huge], tooltip = "Controls  
the text size inside the Awareness Box.")
```

```
// --- Visibility Settings ---
```

```
vaOpacity  = input.int(30, "VA Opacity %", minval = 0, maxval = 100, tooltip =  
"Transparency of histogram rows inside the value area.")
```

```
outOpacity  = input.int(70, "Outside VA Opacity %", minval = 0, maxval = 100,  
tooltip = "Transparency of histogram rows outside the value area.")
```

```
histThickness = input.int(3, "Histogram Thickness", minval = 1, maxval = 5,  
tooltip = "Line thickness used for histogram rows.")
```

```
// --- Colors ---
```

```
COLOR_UP  = #26a69a
```

```
COLOR_DOWN = #ef5350
```

```
COLOR_POC  = #9c27b0
```

```
COLOR_VA   = #6a1b9a
```

```
COLOR_MID  = #fdd835
```

```
COLOR_BG = color.new(#9c27b0, 95)
```

```
AWARENESS_TEXT = "If price opens below VAL, with the POC below the  
midline, that is a \\"Bearish\\" reading at market open.\n\nIf price opens  
above VAH, with the POC above the midline, that is a \\"Bullish\\" reading at  
market open.\n\n- Peace"
```

```
AWARENESS_DISPLAY_TEXT = "VALUE READING AWARENESS\n\nIf price  
opens below VAL,\nwith POC below VA MID:\nBearish reading at market  
open.\n\nIf price opens above VAH,\nwith POC above VA MID:\nBullish  
reading at market open.\n\n- Peace"
```

```
// --- Awareness Box ---
```

```
// Hidden by default; enable it from the script's Inputs settings when needed.
```

```
var table awarenessTable = na
```

```
if barstate.islast and showAwarenessInput
```

```
    if na(awarenessTable)
```

```
        awarenessTable := table.new(awarenessBoxPositionInput, 1, 1, bgcolor =  
color.new(chart.bg_color, 0), frame_color = COLOR_MID, frame_width = 2,  
border_color = COLOR_MID, border_width = 1)
```

```
        table.cell(awarenessTable, 0, 0, AWARENESS_DISPLAY_TEXT, width =  
awarenessBoxWidthInput, text_color = COLOR_MID, text_halign =  
text.align_left, text_valign = text.align_top, text_size = awarenessTextSizeInput,  
text_formatting = text.format_bold, bgcolor = color.new(chart.bg_color, 0))
```

```
// --- Logic: Session Detection ---
```

```
t = time(timeframe.period, sessionTime + ":23456", timezoneInput)
```

```
inSession = not na(t)
```

```
isNewSession = inSession and not inSession[1]
```

```
isSessionEnd = inSession[1] and not inSession
```

```
// --- Data Collection ---
```

```
[ltfO, ltfC, ltfV] = request.security_lower_tf(syminfo.tickerid, "1", [open, close, volume])
```

```
type BarInfo
```

```
    float price
```

```
    float volume
```

```
    bool isUp
```

```
var BarInfo[] currentSessionData = array.new<BarInfo>()
```

```
var int currentSessionStart = na
```

```
var float currentSessionHigh = 0.0
```

```
var float currentSessionLow = 1e10
```

```
var float currentSessionOpen = na
```

```
var int currentSessionOpenBar = na
```

```
var BarInfo[] lastCompletedData = array.new<BarInfo>()
```

```
var int lastSessionStartBar = na
```

```
var int lastSessionEndBar = na
```

```
var float lastSessionHigh = 0.0
```

```
var float lastSessionLow = 0.0
```

```
if isNewSession
```

```
    currentSessionData.clear()
```

```
    currentSessionStart := bar_index
```

```
    currentSessionHigh := high
```

```
    currentSessionLow := low
```

```
    currentSessionOpen := open
```

```
    currentSessionOpenBar := bar_index
```

```
if inSession
```

```
    currentSessionHigh := math.max(currentSessionHigh, high)
```

```
    currentSessionLow := math.min(currentSessionLow, low)
```

```
    if array.size(ltfC) > 0
```

```
        for i = 0 to array.size(ltfC) - 1
```

```
            float lowerClose = array.get(ltfC, i)
```

```
            float lowerVolume = array.get(ltfV, i)
```

```
            float lowerOpen = array.get(ltfO, i)
```

```
            if not na(lowerClose) and not na(lowerVolume)
```

```
                currentSessionData.push(BarInfo.new(lowerClose, lowerVolume,  
lowerClose >= nz(lowerOpen, lowerClose)))
```

```
if isSessionEnd

    lastCompletedData := currentSessionData.copy()

    lastSessionStartBar := currentSessionStart

    lastSessionEndBar := bar_index

    lastSessionHigh := currentSessionHigh

    lastSessionLow := currentSessionLow


// --- Rendering (Only on the Last Bar) ---
var line[] profileLines = array.new_line()
var label[] profileLabels = array.new_label()


if barstate.islast and array.size(lastCompletedData) > 0

    for profileLine in profileLines

        line.delete(profileLine)

    array.clear(profileLines)


    for profileLabel in profileLabels

        label.delete(profileLabel)

    array.clear(profileLabels)


float priceRange = lastSessionHigh - lastSessionLow

if priceRange > 0

    float priceStep = priceRange / rowCount
```

```

float[] rowUpVol = array.new_float(rowCount, 0.0)
float[] rowDownVol = array.new_float(rowCount, 0.0)
float[] rowTotal = array.new_float(rowCount, 0.0)
float totalVol = 0.0

for profileBar in lastCompletedData
    int rowIndex = math.min(rowCount - 1, math.floor((profileBar.price -
lastSessionLow) / priceStep))
    if rowIndex >= 0
        if profileBar.isUp
            rowUpVol.set(rowIndex, rowUpVol.get(rowIndex) +
profileBar.volume)
        else
            rowDownVol.set(rowIndex, rowDownVol.get(rowIndex) +
profileBar.volume)
            rowTotal.set(rowIndex, rowTotal.get(rowIndex) + profileBar.volume)
            totalVol += profileBar.volume

float maxVol = array.max(rowTotal)
if maxVol > 0
    int pocIndex = array.indexof(rowTotal, maxVol)
    float pocPrice = lastSessionLow + pocIndex * priceStep + priceStep / 2.0

float targetVolume = totalVol * valueAreaPct

```

```

float valueAreaVolume = maxVol

int upperIndex = pocIndex
int lowerIndex = pocIndex

while valueAreaVolume < targetVolume and (upperIndex < rowCount - 1
or lowerIndex > 0)

    float upperVolume = upperIndex < rowCount - 1 ?
rowTotal.get(upperIndex + 1) : 0.0

    float lowerVolume = lowerIndex > 0 ? rowTotal.get(lowerIndex - 1) : 0.0

    if upperVolume >= lowerVolume

        upperIndex += 1

        valueAreaVolume += upperVolume

    else

        lowerIndex -= 1

        valueAreaVolume += lowerVolume

float vahPrice = lastSessionLow + (upperIndex + 1) * priceStep
float valPrice = lastSessionLow + lowerIndex * priceStep
float vaMidPrice = valPrice + (vahPrice - valPrice) / 2.0

// Draw Histogram.

for i = 0 to rowCount - 1

    float rowY = lastSessionLow + i * priceStep + priceStep / 2.0

    float rowVolume = rowTotal.get(i)

```

```

    if rowVolume > 0

        int totalLength = math.round((rowVolume / maxVol) * histWidth)

        int upLength = math.round((rowUpVol.get(i) / rowVolume) *
totalLength)

        int transparency = i >= lowerIndex and i <= upperIndex ? vaOpacity :
outOpacity

        profileLines.push(line.new(lastSessionStartBar, rowY,
lastSessionStartBar + upLength, rowY, color = color.new(COLOR_UP,
transparency), width = histThickness))

        profileLines.push(line.new(lastSessionStartBar + upLength, rowY,
lastSessionStartBar + totalLength, rowY, color = color.new(COLOR_DOWN,
transparency), width = histThickness))

// Draw extension lines from the end of the completed session.

    profileLines.push(line.new(lastSessionEndBar, pocPrice, bar_index +
50, pocPrice, color = COLOR_POC, width = 2, extend = extend.right))

    profileLines.push(line.new(lastSessionEndBar, vahPrice, bar_index + 50,
vahPrice, color = COLOR_VA, style = line.style_dashed, width = 2, extend =
extend.right))

    profileLines.push(line.new(lastSessionEndBar, valPrice, bar_index + 50,
valPrice, color = COLOR_VA, style = line.style_dashed, width = 2, extend =
extend.right))

    profileLines.push(line.new(lastSessionEndBar, vaMidPrice, bar_index +
50, vaMidPrice, color = COLOR_MID, style = line.style_dotted, width = 2,
extend = extend.right))

```

```
profileLabels.push(label.new(bar_index + 5, pocPrice, "POC", color =  
#00000000, textcolor = COLOR_POC, style = label.style_label_left, size =  
labelSize))
```

```
profileLabels.push(label.new(bar_index + 5, vahPrice, "VAH", color =  
#00000000, textcolor = COLOR_VA, style = label.style_label_left, size =  
labelSize))
```

```
profileLabels.push(label.new(bar_index + 5, valPrice, "VAL", color =  
#00000000, textcolor = COLOR_VA, style = label.style_label_left, size =  
labelSize))
```

```
profileLabels.push(label.new(bar_index + 5, vaMidPrice, "VA MID", color  
= #00000000, textcolor = COLOR_MID, style = label.style_label_left, size =  
labelSize))
```

```
// Display a compact value-reading text box at the NY session open.
```

```
if showReadingInput and inSession and not na(currentSessionOpen)  
and not na(currentSessionOpenBar)
```

```
bool bullishReading = currentSessionOpen > vahPrice and pocPrice >  
vaMidPrice
```

```
bool bearishReading = currentSessionOpen < valPrice and pocPrice <  
vaMidPrice
```

```
bool mixedReading = (currentSessionOpen > vahPrice and pocPrice  
<= vaMidPrice) or (currentSessionOpen < valPrice and pocPrice >=  
vaMidPrice)
```

```
if bullishReading or bearishReading or mixedReading
```

```
string readingText = bullishReading ? "BULLISH VALUE  
READING\nOpen > VAH • POC > VA MID" : bearishReading ? "BEARISH
```

VALUE READING\\nOpen < VAL • POC < VA MID" : "**MIXED / PROBABILITY
MAGNET**\\nOpening location and POC disagree"

string readingTooltip = bullishReading ? "Bullish Value Reading at NY
open.\\n\\nIf price stays above VAH, then Bullish Acceptance." :
bearishReading ? "Bearish Value Reading at NY open.\\n\\nIf price stays below
VAL, then Bearish Acceptance." : "Mixed Value Reading at NY open.\\n\\nThe
opening location and POC disagree. The POC may act as a probability
magnet, but it is not a guaranteed target."

float readingY = bullishReading ? vahPrice + priceStep * 0.5 :
bearishReading ? valPrice - priceStep * 0.5 : pocPrice + priceStep * 0.5

labelStyle = bullishReading ? label.style_label_down :
bearishReading ? label.style_label_up : label.style_label_left

profileLabels.push(label.new(currentSessionOpenBar, readingY,
readingText, color = color.new(chart.bg_color, 15), textcolor = COLOR_MID,
style = labelStyle, textalign = text.align_left, tooltip = readingTooltip, size =
labelSize))

// --- Background Highlighting ---

bgcolor(inSession ? COLOR_BG : na)